



RAPTOR RUBBER

CHUTEX - RED Rubber Sheet

RAPTOR Red Chutex Natural Rubber has excellent cut and tear resistance. Used extensively where high abrasion resilience is required.

Typical applications include lining of hoppers, bins and chutes. Other applications are vibration equipment, silos, conveyor scrapers, hydro-cyclones and vacuum trucks.
ASTM Line call : D2000 M4 AA430 A13 B13 F17



Standard Sizing

PRODUCT CODE	THICKNESS	ROLL WIDTH	ROLL LENGTH	WEIGHT
R - 530 045 040	3.0 mm	1200 mm	10 meters	3.19 kgs/m ²
R - 530 045 053	4.8 mm	1200 mm	10 meters	4.78 kgs/m ²
R - 530 045 060	6.0 mm	1200 mm	10 meters	6.31 kgs/m ²
R - 530 045 082	9.5 mm	1500 mm	10 meters	9.49 kgs/m ²
R - 530 045 092	12 mm	1500 mm	10 meters	12.58 kgs/m ²

Specification Table

SPECIFICATION PROPERTIES	TEST METHOD	TEST RESULT
TEMPERATURE RANGE	ASTM D2137	-40 °C to +75 °C
HARDNESS	ASTM D2240	SHORE A : 42
100% MODULUS	ASTM D-412	150 psi
TENSILE STRENGTH	JIS K6301	210 kg/cm ²
ELONGATION AT BREAK	JIS K6301	600 %
TEAR STRENGTH	ASTM D-412	50 kg/cm
DIN ABRASION	-	< 40 mm ³

specifications

For more information and product range please visit www.raptorrubber.com.au

Please contact your local distributor ;
Welco Industrial Rubber Pty Ltd
Tel : 03 9334 5962 (Sales)
E: sales@welcorubber.com.au



RAPTOR RUBBER